



## PP Vertical Laminar Flow Cabinet



### ADVANTAGE


1. Made of PP material, integrally welded
2. Resistant to strong acid, alkali and strong corrosion
3. With memory function in case of power-failure
4. Interlock function: UV Lamp and blower, LED Lamp
5. The work surface is seamlessly welded with 12mm thick PP plate, which is convenient for overall cleaning



**LCD Display**  
Airflow velocity, UV timer, UV work time, system work time, real time.



**Waterproof Socket**  
Waterproof sockets is located in the back panel, for optimum convenience of using small devices inside the cabinet.



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination.



**Footmaster Caster**  
Universal caster with brake and leveling feet

### TECHNICAL PARAMETERS

Model	BKCB-800P
External Size (W*D*H)	800*710*1800mm
Internal Size (W*D*H)	780*540*550mm
Work Surface Height	750mm
Material	Main Body: Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion. Work Table: Seamlessly welded with 12mm thick PP plate
Front & Side Windows	5mm toughened glass, anti-UV, Manual
Pre-Filter	Polyester fiber, Washable
Filter Size (W*D*H)	560*340*46mm
HEPA Filter	99.995% efficiency at 0.3μm
Airflow Velocity	0.3~0.5m/s
Noise	≤65dB
Max. Opening	400mm
UV Lamp	20W*1, Emission of 253.7 nanometers, with UV time
LED Lamp	8W
Illumination	≥350lx
Caster	Foot master Caster
Waterproof Socket	Two, total load≤500W
Consumption	650W
Standard Accessory	UV lamp; Led lamp; Base stand; Waterproof socket*1
Power Supply	220V,50/60Hz (Standard); 110V,60Hz(Optional)
Package Size (W*D*H)	1000*900*1300mm
Gross Weight	90kg